

531,023

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036500 A2

(51) International Patent Classification⁷: **G06T 5/00**

(21) International Application Number:
PCT/IB2003/004142

(22) International Filing Date:
12 September 2003 (12.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02079278.4 16 October 2002 (16.10.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TRUYEN, Roel**

[BE/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **LOBREGT, Steven** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **GERRITSEN, Frans, A.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


(74) Agent: **SCHOUTEN, Marcus, M.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: **HIERARCHICAL IMAGE SEGMENTATION**



(57) Abstract: An apparatus 1000 includes an input 1010 for receiving an N-dimensional signal, $N \geq 2$. A storage 1030 stores a composite model of a composite structure for estimating parameters of the model with respect to the signal. The composite model is based on constituent models 210-290 that each correspond to a constituent structure in the signal and that are incorporated in the composite structure. Each constituent model is designated for estimating parameters of the constituent model with respect to the signal based on prior knowledge of the constituent structure. At least two of the constituent models are based on differing technologies. Each constituent model is provided with a uniform interface for controlling the constituent model and for retrieving parameters estimated by it. A processor 1020 is programmed to estimate the model parameters by controlling the constituent models to estimate their parameters; to retrieve estimated parameters from the constituent models; and to estimate parameters of the model in dependence on the retrieved parameters.

WO 2004/036500 A2